

Product Highlights

Flexible operation

- Small turning radius, flexible operation in narrow spaces
- Standard forklift slot for efficient equipment transportation
- Folding guardrails for easy transport

Reduced maintenance costs

- Double-door design for easy maintenance
- Troubleshooting for quick fault diagnosis
- Highly quality parts and components

More reliable performance

- Battery voltage early warning to ensure battery life
- Bumper rail protection
- Pothole protection reporting and horizontal protection system give peace of mind during operation

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresis painting technology
■ 4×2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

SINOBOOM

Sinoboom Intelligent Equipment Co Ltd

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park,
Changsha, Hunan, China, 410600

🌐 www.sinoboom.com

✉ sales@sinoboom.com

Hydraulic Series Scissor Lifts

1012(3346)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

Model		1012(3346)	
Dimensions		Metric	US
Max Working Height		12m	39'4.5"
A	Max Platform Height	10m	32'10"
B	Max Horizontal Extension	0.9m	3'
C	Length-Stowed	2.39m	7'10"
D	Width-Stowed	1.15m	3'9"
Height-Stowed(Rail Folded)		1.86m	6'1"
E	Height-Stowed (Rail Unfolded)	2.48m	8'2"
F	Wheelbase	1.85m	6'1"
Ground Clearance		0.1m	4"
Platform Dimensions (L×W×H)		2.25m×1.15m×1.1m (7'5"×3'9"×3'7")	
Performance			
Platform Allowable Occupants (Indoor/Outdoor)		2 persons/1 person	
Platform Capacity		320kg	705.6 lbs
Drive Speed-Stowed		3.2km/h	2mph
Drive Speed-Raised		0.8km/h	0.5mph
Elevation Time(Unloaded)		53s~58s	
Descent Time(Unloaded)		40s~45s	
Gradeability		25%	
Turning Radius(Inside/Outside)		0/2.35m	0/7'8.5"
Tilt Rating (Front to Back/Side to Side)		3°/1.5°	
Tyres-solid		380×125mm(15×5")	
Power			
Batteries		6V×4/240Ah	
Power Source		24V DC	
Drive Mode		2WD, front-wheel	
Charger Input		100~240V AC	
Charger Output		25A	
Brake		2 rear wheel	
Hydraulic System Capacity		35L	7.7gal
Weight			
Weight(Indoor/Outdoor)		2,570kg	5,667lbs
Weight(Indoor Only)		2,380kg	5,248lbs
Standards Compliance		ISO/CE/ANSI/CSA/AS/CU-TR/KCS	

